

Model 75-1

BREAD BAGGER



West Coast Sales & Manufacturing

19216 S. Laurel Park Road Rancho Dominguez, CA 90220

Tel: 310.635.8121 • Fax: 310.635.8171

sales@ubeusa.com

www.ubeusa.com



The Model 75-1 combines years of step - by - step improvements into a low maintenance reciprocating bagger with reliability at high speed.

Specifications

Bagging speed

up to 75 loaves per minute

Min. / max. loaf size

7" x 3" x 3" / 16" x 6" x 6" (l-w-h)

[177 x 76 x 76mm / 406 x 152 x 152 mm] (l-w-h)

Electrical

208/230/380/460 v, 3 ph, 50/60 hz

Air requirements

6 cfm @ 90 psi dry filtered

Features

- Tubular stainless steel frame and aluminum guards
- Drive system with stronger gear box for high speed production
- Cams designed for high speed, CNC machined and hardened
- Long life high torque pneumatic clutch/brake
- Redesigned scoop slide allows higher speed with new bearing material
- Slide shaft with 72 Rockwell C hardness and 8 RMS finish
- Dual bag magazine with top mounted bag inflator jet
- Independent overload clutches on infeed, outfeed and slicer drives
- Solid state control circuit with proximities for cams and door safeties

- Automatic bag changer with programmable controller
- Digital speed indicator

Options

- Automatically synchronized speed control between multiple machines
- Extended discharge conveyor or special length infeed
- CE Approval, guards and coded magnetic door switches
- UL Approval
- CSA Approval
- Available in metric construction (where possible)

Technical Layout:

