



UNITED BAKERY EQUIPMENT CO.  
Engineering Excellence Since 1966

# MODEL 175

## Wrapper



### UBE Model 175 Wrapper

The UBE 175 Wrapper improves on the bread wrapping technology of the past 80 years with features that update our machine to the twenty first century.

- ROI: UBE original engineered quality OEM Parts. Engineered from the ground up to maximize ROI.
- Providing innovative quality solutions to your slicing and bagging needs since 1966.
- We are experts with the next generation of PLC motion control.
- See the future of slicers and baggers from the industry leader.
- Our new machines have a more simplified design to increase reliability and ease of operation, as well as reduce maintenance and improve sanitation.



UNITED BAKERY EQUIPMENT CO.  
Engineering Excellence Since 1966

## Specifications

Specifications vary by product and application. Please contact our sales office about product varieties and speeds.

Wrapper max. speed  
Up to 65 loaves per minute

Minimum Loaf Sizes  
3" x 3" x 6" / [76.2 x 76.2 x 152.4 mm]  
(w-h-l)

Maximum loaf sizes  
8" x 5-3/4" x 16" / [203 x 146 x 406 mm]  
(w-h-l)

Electrical  
208/230 volts 60 amp, 3 phase,  
50/60 Hz- or- 480 volts, 40 amps

Air Requirements  
5 CFM @ 80 PSI,  
(minimum 3/8" air hose)

United Bakery Equipment  
Sales and Manufacturing  
15315 Marquardt Ave.  
Santa Fe Springs, CA 90670  
Tel: 310.635.8121  
Fax: 310.635.8171  
sales@ubeusa.com  
parts@ubeusa.com

[www.ubeusa.com](http://www.ubeusa.com)

© United Bakery Equipment, Inc. 2019

Proudly  
manufactured  
in the USA



UBE builds the Model 175 Wrapper for each customer's particular needs. Over 1000 installations required numerous customer driven innovations. Your machine may vary from this typical unit illustrated. UBE wants to meet with you and design your new line.

## Features

- Right/Left hand infeeds available
- Wrapped bread bypass available (option)
- Tubular stainless steel frame (paint free construction)
- All bushings are no lube, non-metallic bushings
- All bearings have remote lubrication fittings (option)
- Maintenance free pusher slide
- Quality drive components
- All new improved top transfer design
- Traction vacuum film suction
- Servo driven width adjustment
- Servo drive paper drive
- Servo drive pump roller
- Servo driven width crossfeed
- Servo driven main drive

## Options

- Bagger Bypass conveyor
- CE Approval, guards and coded magnetic door switches
- UL Approval
- CSA/UL Approval
- Available in metric construction (where possible)
- Right/Left hand infeeds available
- Wrapped bread bypass available (option)
- Tubular stainless steel frame (paint free construction)
- All bushings are no lube, non-metallic bushings
- All bearings have remote lubrication fittings (option)
- Maintenance free pusher slide

## Technical Layout

